


**SEPARATOR MATERIAL, ITS MANUFACTURING METHOD, AND BATTERY**

**Patent number:** JP2003059482  
**Publication date:** 2003-02-28  
**Inventor:** YAMAMOTO HIROYUKI; AOKI NOBUO; TANAKA TOMOFUMI; KIDA TATSUNOBU; KAMISASA TOSHIO  
**Applicant:** DAIWA SPINNING CO LTD;; DAIWABO POYTECH KK  
**Classification:**  
- international: H01M2/16; D04H1/42; H01G9/02; H01M10/30; D06M11/55  
- european:  
**Application number:** JP20020134535 20020509  
**Priority number(s):** JP20010138795 20010509; JP20020134535 20020509

[Report a data error here](#)

**Abstract of JP2003059482**

**PROBLEM TO BE SOLVED:** To provide a separator material having high denseness, not obstructing the passage of an electrolyte or gas, having high short resistance, suppressing increase in internal resistance and internal pressure, and having long charge/ discharge cycle life, and provide the manufacturing method of the separator material. **SOLUTION:** This separator material is a nonwoven fabric containing divided type composite fibers composed of polyolefin resin having a plurality of different components. The divided type composite fibers are divided into very fine fibers 1 having a fineness of less than 0.5 dtex having a divided almost trapezoidal fiber cross section and a very fine fiber bundle 2 bundling the very fine fibers. This separator material makes water dispersed slurry with constituting fibers containing the divided type composite fibers, a wet type paper making web is prepared by dividing a part of the dividing type composite fibers, formed in a nonwoven fabric by drying, and the nonwoven fabric is pressed with a pair of rollers having a temperature higher than 40 deg.C and lower by 30 deg.C or more than a temperature at which constituting fibers are melted so as to have a thickness of 150  $\mu$ m or less.



Data supplied from the **esp@cenet** database - Worldwide